



TECHNICAL DATA

MASSES

Net mass	66 kg
Operating mass	67 kg

COMPACTION

Impact force, kN	16 kN
Vibration frequency	10.0 – 11.8 Hz

TRACTION

Max. area coverage	336 m ²
Max. working speed	20 m/min

ENGINE

Manufacturer/Model	Honda GX 100
Number of cylinders	1
Type	Air cooled gasoline
Emissions according to	Stage V /CARB Phase III
Rated power	2.3 kW
Fuel tank capacity	3 l
Fuel consumption /h, avg.	0.9 l

DRIVE SYSTEM



Drive system	Mechanical
--------------	------------

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.



DIMENSIONS



DIMENSIONS

B. Width	350 mm
H. Height	1030 mm
L. Length	728 mm
L1. Length	335 mm
W. Basic shoe width	280 mm

STANDARD EQUIPMENT

- Low vibration handle
- Dual stage fuel filter system
- Air filter
- Auto oil level check before start
- Engine protection covers
- One knob to start or stop both engine & fuel
- Infinitely variable frequency
- Recoil starter
- Loading aid rollers on handle
- One point lift

OPTIONAL EQUIPMENT

- Hour and rpm display
- Puncture proof transport wheels
- Foot widths & extensions
- Service kit

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.